


Fiber Patchcord

Features	
Low Insertion Loss High Return Loss & High Repeatability	
Application	
LAN, Data network CATV Network Telecommunication	

Specifications:

Parameter		Value				
Connector Type		FC,SC,ST, LC, MU etc				
Operating wavelength (nm)		1310/1550	980/1060	780/850	633	850/1310
Fiber Type		Single Mode				Multi -Mode
		SMF-28e	HI1060 or HI1060Flex	HI780C or SM800	SM600	50/125 or 62.5/125 or 105/125
Insertion loss (dB)		≤0.25	≤0.4	≤0.8	≤1.5	≤0.30
Return loss (dB)	UPC	≥50	≥50dB	≥50dB		≥40
	APC	≥60	≥60dB	≥60dB		/
Repeatability (dB)		≤0.1	/	/	/	≤0.1
Changeability (dB)		≤0.2	/	/	/	≤0.2
Durability		≥1000				
Operating temperature (°C)		-40 ~ + 85				

Ordering Information:

JP	Connector (Input)	Connector (Output)	Wavelength	Pigtail Type	Fiber Type	Length
	NE=None FA=FC/APC FC=FC/UPC SA=SC/APC SC=SC/UPC LC=LC/UPC LA=LC/APC MU=MU/UPC	NE=None FA=FC/APC FC=FC/UPC SA=SC/APC SC=SC/UPC LC=LC/UPC LA=LC/APC MU=MU/UPC	633 780 850 980 1064 1310 1550	250=250um bare fiber 900=900um loose tube 900T=900um tight buffer 2000=2mm loose tube 2000C=2mm cable 3000=3mm loose tube 3000C=3mm cable	1=SMF-28e 2=50/125 MM 3=62.5/125 MM 4=HI1060Flex X=Other	1=1m X=Specify