









## Hybrid Adapter

<b>Features</b>	
Low Insertion Loss High Repeatability	
<b>Application</b>	
LAN, Data network CATV Network Telecommunication	

**Specifications:**

Insertion Loss	≤0.2 dB
Plug and unplug force (g/f)	200-600
Durability	1000times
Operating Temperature	-40°C to +75°C

Part Number	Description	Photo
AD-LC/FC-SP01	LC-FC Metal Adapter	
AD-LC/SC-SP02	LC-SC Adapter	
AD-FC/SC-SP03	FC-SC adapter with square flange	
AD-FC/SC-SP04	FC-SC Adapter with rectangular flange	
AD-FC/SC-SP05	FC-SC Duplex adapter	
AD-FC/ST-SP06	FC-ST Adapter with rectangular Flange	

<p><b>AD-FCF/SCM</b></p>	<p><b>Adaptor-FC/Female-SC/male</b></p>	
<p><b>AD-SC/ST-SP07</b></p>	<p><b>SC-ST Adapter</b></p>	
<p><b>AD-SC/ST-SP08</b></p>	<p><b>SC-ST Duplex adapter</b></p>	
<p><b>AD-FCF/LCM/SM-SP01</b></p>	<p><b>FC/Female to LC/Male single mode adapter</b></p>	
<p><b>AD-FCF/LCM/MM-SP02</b></p>	<p><b>FC/Female to LC/Male Multi-mode adapter</b></p>	