

Mini Size Single Mode Standard Coupler

Features	
Low excess loss & low IL & low PDL Mini Size High stability and reliability	
Application	
Mini size EDFA Mini size transmitter/receiver module Optical communication systems Testing instruments	

Specifications:

Parameter	Grade P	Grade A	
Operating Wavelength (nm)	1310 or 1550, others on request		
Operating Bandwidth (nm)	±15		
Typical Excess Loss (dB)	0.07	0.10	
Insertion Loss (dB)	50/50	≤3.5	≤3.7
	40/60	≤4.5/2.7	≤4.8/2.9
	30/70	≤5.8/2.0	≤6.1/2.1
	20/80	≤7.7/1.25	≤8.0/1.3
	10/90	≤11.2/0.7	≤11.8/0.85
	5/95	≤14.5/0.45	≤15.0/0.55
	2/98	≤18.5/0.3	≤19.2/0.35
	1/99	≤21.5/0.25	≤22.2/0.3
PDL (dB)	≤0.1	≤0.15	
Directivity (dB)	≥55		
Operating Temperature (°C)	-40 ~ +85		

Package Information

Configuration	1x2 or 2x2
Fiber Length	1m, others on request
Fiber Type	SMF-28e
Pigtail Type	250µm bare fiber
Dimensions(mm)	φ2.4×25; φ3.0×30; φ3.0×35;

Ordering Information

CP	Type	Grade	Port Type	Wavelength	Coupling Ratio	Pigtail Type	Fiber Type	Length	Connector	Package
	S=SM standard	P A	1x2 2x2	1310 1550	1/99 2/98 3/97 50/50	250=250um fiber	1=SMF-28e	1= 1m X=Other	NE=None FA=FC/APC FC=FC/UPC SA=SC/APC SC=SC/UPC LC=LC/UPC LA=LC/APC XX=Others	2.4x25 3x30 3x35